











# INNOMINITM T°C mixER

Temperature Controlled Mixer

Phone: 1-800-932-5000



avantorsciences.com

Any prices, product, and/or services details are current when published and subject to change. Offers subject to product availability. Void where prohibited by law or company policy. Any claims concerning products manufactured by third parties are the sole claims of the manufacturer and not those of Avantor or its affiliates. All products are subject to the terms and conditions of sale of Avantor or its affiliates, including the applicable limitations of liability contained therein. The information herein should not be considered a warranty of any kind. Please carefully review any product information sheets and safety information for the product. Trademarks are owned by Avantor, Inc. or its affiliates, unless otherwise noted. | Visit vwr.com avantorsciences.com to view our privacy policy and additional disclaimers. © 2025 Avantor, Inc. All rights reserved.



# T°CmixER-A

# Temperature Controlled Mixer

T°CmixER-A is a thermostatic mixer with an independent control system, which is indigenously developed by VELSSON. It could meet the requirements of heating, cooling and mixing of liquid samples in a variety of experimental scenarios. It has the advantages of high precision, stable performance, simple operation and could be embedded into automation systems.



### Features

#### Precise temperature control

Equipped with a high–precision temperature sensor and intelligent temperature control system, T°CmixER–A has a temperature range of 0–100°C and great accuracy of 0.2°C, ensuring stable experimental conditions and accurate results

#### Condensation prevention

The hot cover (optional) effectively prevents the generation of condensation, and the unique condensation collection device effectively collects and removes condensation water, avoiding the risk of circuit failure caused by condensation and ensuring the temperature control stability

#### Flexible operation

With an intuitive operation interface, T°CmixER-A is very simple for users to get started with. It also supports multiple remote operating modes, including manual, scheduled and continuous operation. Temperature, time and rotate speed could all be set with one click

#### Efficient mixing

T°CmixER−A could quickly and evenly mix samples without unevenness and stratification, owing to the unique and efficient mixing system design

#### Automated control

The equipment could work automatically through preset programs or remote control, and could be easily integrated into existing automation systems to improve experimental efficiency and repeatability

#### Excellent compatibility

T°CmixER-A has excellent compatibility and could be adapted to different types of samples, containers and consumables, which users could replace accoring to the needs of various experimental scenarios. It is versatile, thus saves time and trouble for you







Main view

Right view

Left view

## | Application scenarios



Cell culture



Nucleic acid extraction



Enzymatic reaction



Chemical reaction



Sample storage and handling



Protein crystallization



PCR experiment



Food safety testing



Environmental monitoring

## Specifications

Dimensions	200*200*140mm (7.9*7.9*5.6 inch)	Net weight	7KG
Function	Heating, cooling, mixing	Temp. control range	0~100°C
Temp. control accuracy	≤ ± 0.2°C	Display accuracy	0.1℃
Heating/cooling speed	±5℃/min	Module temperature uniformity	≤ ± 0.3°C
Time setting	1 ~ 99h59min59s / ∞	Speed range	200~2,000rpm
Horizontal amplitude	3mm	Scheduled power on/off	Supported
Scheduled start	Supported	Automatically run at boot	Supported
Automatic recovery after power outage	Supported	Consumable base replacement	Parallel replacement, replacement time ≤5min
Automatic preheating	Supported	Instant mixing	1s instant mixing
Interval mixing	Minimum 1s interval mixing of 4~45°C	Programming function	≥10 groups can be programmed and saved at the same time
Multi-point loop	Up to 5 points and a maximum of 99 loop runs	Automatic positioning	Automatic return to origin, automatic pick and place
Interface protocol	OPC-UA/CAN		
Remote control	Remote automatic opening and closing of doors, adjustment of functional parameters, and connection with automation systems		